

SPECIFICATION

TO ALL WHOM IT MAY CONCERN:

BE IT KNOWN THAT I, OSAMU SUZUKI, a citizen of Japan residing at Kanagawa, Japan has invented certain new and useful improvements in

NETWORK FACSIMILE MACHINE WITH IMPROVED USABILITY
of which the following is a specification:-

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention generally relates to network facsimile machines, and more particularly to
5 a network facsimile machine that can set the title of an electronic mail message at the time of transmitting data using an electronic mail system.

2. Description of the Related Art

10 Facsimile machines, which can transmit and receive image data such as characters and drawings, have been widely used and are familiar business machines. The conventional facsimile machines include network facsimile machines (hereinafter
15 referred to as "facsimile machines") having the function of transmitting and receiving the data of an electronic mail message (also referred to as an "e-mail") via the Internet. Such data is hereinafter referred to as "mail data."

20 Such conventional facsimile machines include, for instance, the facsimile machine disclosed in Japanese Laid-Open Patent Application No. 2000-341465. This facsimile machine stores at least one of the destination address and the transmission title of an
25 e-mail as transmission history data. This facsimile

machine also stores data input previously by an operator. When the operator inputs a desired destination address or transmission title, the desired destination address or transmission title can
5 be selected from the transmission history data or the previously input data. As a result, the operability of the facsimile machine is improved.

According to this conventional facsimile machine, however, the operator is required to perform
10 an input operation for specifying the transmission title, that is, the subject name of the e-mail (hereinafter simply referred to as a "subject name") whenever inputting the destination address or the transmission title. Therefore, even if it is
15 possible or sufficient to use the same subject name for every transmission, the operator is required to perform the input operation for specifying the subject name for each transmission, which poses a problem to the operator.

20

SUMMARY OF THE INVENTION

Accordingly, it is a general object of the present invention to provide a facsimile machine in which the above-described disadvantage is eliminated.

25

A more specific object of the present

invention is to provide a facsimile machine with a
mail transmission and reception function, the
facsimile machine being made easy to use by
incorporating the function of automatically
5 specifying the subject name.

The above objects of the present invention
are achieved by a network facsimile machine
including: an image information scanner part scanning
image information of an original and outputting image
10 data; a display part displaying information, the
display part including a predetermined display unit;
a part transmitting and receiving image data via a
public network; a part transmitting and receiving
mail data via a network; a subject name registration
15 part registering one or a plurality of subject names
insertable into an electronic mail message for
transmitting the mail data; a subject name
specification determination part determining whether
one of the subject names is specified for the mail
20 data to be transmitted; and a subject name specifying
part automatically specifying one of the subject
names registered in the subject name registration
means as the transmission subject name of the mail
data if the subject name specification determination
25 part determines that none of the subject names is

specified for the mail data.

According to the above-described network facsimile machine, the subject name can be automatically specified without the operator performing an operation for specifying the subject name. Therefore, the network facsimile machine is easy to use.

BRIEF DESCRIPTION OF THE DRAWINGS

10 Other objects, features and advantages of the present invention will become more apparent from the following detailed description when read in conjunction with the accompanying drawings, in which:

FIG. 1 is a diagram showing a communication network for data communication using facsimile machines according to the present invention;

FIG. 2 is a block diagram showing the facsimile machine according to the present invention; and

20 FIGS. 3A and 3B are flowcharts showing a procedure for a subject name determination operation performed by the facsimile machine according to the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

A description is given below, with reference to the accompanying drawings, of an embodiment of the present invention.

5 FIG. 1 is a diagram showing a communication network 100 for data communication using facsimile machines 20 and 30 according to the present invention. In FIG. 1, the communication network 100 includes the facsimile (FAX) machines 20 and 30 and personal
10 computers (PCs) 21 and 31 that are connected via a network 15 such as the Internet. In the communication network 100, mail data is transmitted from the facsimile machine 20 or the PC 21 and received by the facsimile machine 30. The PC 31 can
15 also be a destination to which the mail data is transmitted.

 When the facsimile machine 20 or the PC 21 transmits an e-mail, its mail data is transmitted via the network 15 to be received by the facsimile
20 machine 30. The facsimile machine 30 prints out the received mail data on a predetermined sheet of paper. The e-mail transmitted and received via the communication network 100 is composed mainly of document information transmitted as a message.
25 Information such as image information or voice

information is attached to the document information as an attachment file. While being transmitted through the network 15, the e-mail has the document information as well as the attached information such as image or voice information converted into a text format. In the following description, the facsimile machine 20 is taken as an example of the facsimile machine according to the present invention.

Next, a description is given, with reference to FIG. 2, of the basic internal configuration of the facsimile machine 20. FIG. 2 is a block diagram showing the facsimile machine 20. Referring to FIG. 2, the facsimile machine 20 includes a central processing unit (CPU) 1, a read-only memory (ROM) 2, a random access memory (RAM) 3, an operation display 4, an image information scanner 5, an image information output 6 such as a plotter, a coder-decoder (CODEC) 7, an image information storage 8, a modem 9, a PSTN (public switched telephone network) controller 10, and a LAN controller 11, which are connected to a data bus 12.

The CPU 1, which controls the operation of the entire facsimile machine 20 in accordance with a program stored in the ROM 2, operates as various means characterizing the present invention.

The ROM 2 is read-only storage means for storing the basic program for the facsimile machine 20 executed by the CPU 1, programs for realizing the functions characterizing the present invention, a communication control procedure, a network control procedure, a mail data transfer procedure, and permanent data. The RAM 3, which is used as the data region of the programs, operates as subject name registration means for registering the subject name for each of below-described user codes.

The operation display 4, which includes operation keys composed of mechanical or touch-panel keys having predetermined alphanumeric keys, is operation input means for exchanging data with the CPU 1 via the data bus 12. The operation display 4 inputs information necessary for using the facsimile machine 20 to the CPU 1 by the operation of the operation keys. Such information includes: operations necessary for the facsimile transmission of image data or the transmission of mail data, such as the inputting of the facsimile number of a transmission destination, start and stop operations, the setting of the subject name, and the inputting of the mail address of a transmission destination; and the confirming of transmission and reception status.

The operation keys include: numeric keys for inputting facsimile numbers; start, stop, redial, and one-touch keys used in a series of operations performed at the time of facsimile transmission; and
5 speed dial keys for selecting abbreviated numbers.

Further, the operation display 4 also serves as display means including: an LED display unit; a display unit such as a liquid crystal display (LCD) for displaying the subject name and the mail address
10 of a transmission destination input through the operation keys, the current operating state, and time; and a sounding device such as a buzzer. The operation display 4 operates in response to an instruction input from the CPU 1.

15 The image information scanner 5 is image information scanning means for inputting image data by scanning, by an image sensor, the image of an original that is a paper sheet on which characters and drawings are formed, and converting the scanned
20 image into an electrical signal. The image information scanner 5, which is also referred to as a scanner part, may be an image scanner using a charge-coupled device (CCD).

The image information output 6 is writing
25 means including a mechanism for forming and printing

an image on a paper sheet based on input image
information representing received image and mail data,
and the reception results (for instance, information
such as the facsimile number of a transmitter and
5 time of reception). The image information output 6
may be of any type that allows image recording on a
paper sheet, such as an electrophotographic, ink-jet,
or toner-jet type.

The CODEC 7 encodes and decodes input image
10 data. The CODEC 7 also compresses the input image
data, and stores the compressed image data in the
image information storage 8. Further, the CODEC 7
decompresses the compressed input image data, and
inputs the decompressed image data to the image
15 information output 6 as raw data.

The image information storage 8 is image
information storage means for storing image data read
from an original to be transmitted and received image
and mail data. The image information storage 8 is
20 adapted to store the image data at least temporarily,
and stores as files a plurality of received message
data items and message data items to be transmitted.
For instance, a magnetic disk unit is employed as the
image information storage 8. The modem 9 performs
25 modulation and demodulation necessary for the

transmission and reception of image or mail data.

The PSTN controller 10, receiving an instruction from the CPU 1, controls a network control unit (NCU) (not shown in the drawing) to
5 establish connection with a subscriber line PSTN and control communications with a communication terminal at the other end during the facsimile transmission and reception of image data. Further, the PSTN controller 10 operates the modem 9 to demodulate the
10 received (modulated) data from the communication terminal at the other end and to modulate data to be transmitted. The PSTN controller 10 also detects the pulses of the ringing voltage detected in the NCU, a DTMF (dual tone multi-frequency) signal, and a tone
15 signal, and sets up a call at the time of transmission.

The LAN controller 11, which transmits and receives mail data via the network 15, is network control means composed of an LSI that decodes
20 received data, encodes data to be transmitted to the network 15, and performs buffering of a frame to be transmitted or a received frame.

Next, a description is specifically given, with reference to FIGS. 2, 3A and 3B, of functions of
25 the facsimile machine 20 having the above-described

configuration.

In the facsimile machine 20, the CPU 1 reads a predetermined program stored in the ROM 2 and operates each component, thereby realizing various functions characterizing the present invention. FIGS. 3A and 3B are flowcharts showing a procedure for an operation of determining the subject name, which operation characterizes the facsimile machine 20. This operation is referred to as a "subject name determination operation."

While performing the subject name determination operation shown in FIGS. 3A and 3B, the facsimile machine 20 causes the CPU 1 to operate the image information scanner 5 so as to read the image information of a set original and create mail data to which the read image data is attached as an attachment file. The operator performs various operations for specifying the address of the facsimile machine 30 or the PC 31 to which the mail data is to be transmitted, and starts a transmission operation by pressing down the start key. Then, the CPU 1 of the facsimile machine 20 starts the subject name determination operation for the created mail data in accordance with the program stored in the ROM 2.

Once the subject name determination operation is started, in step S1 of FIG. 3A, the CPU 1 operates as subject name determination means to determine whether the operator has specified the subject name for the mail data in the previously performed various operations. If the CPU 1 determines in step S1 that the operator has specified the subject name, the CPU 1 terminates the subject name determination operation, and the subject name specified in the previously performed various operations is inserted in the mail data.

If the CPU 1 determines in step S1 that the subject name has not been specified, in step S2, the CPU 1 operates as identification code determination means to determine whether a user code has been specified. The user code is an identification code characteristic of the user (operator). The user code is used to manage a communication history from the specifying of the user code when the operator specifies the user code at the time of transmitting mail data. For instance, the user code is used to determine the number of communications (transmissions) performed by each operator. It is possible to register a plurality of subject names for each user code and determine which one of the

registered subject names to use as a below-described transmission subject name. It is also possible to register a plurality of subject names that are common to the user codes and determine which one of the

5 registered subject names to use. That is, it is possible to register a subject name specified for preferential use so that the specified subject name can be used as the transmission subject name.

Further, it is also possible to register a name for

10 each user code. Furthermore, if the user code is specified as an F code by a transmitter at the other end at the time of transmitting mail data, it is also possible to register for the user code a distribution destination to which the mail data is distributed.

15 The user code, together with the above-described information, is stored in the RAM 3. The operator can select a subject name to be specified for preferential use from the registered subject names by operating the operation display 4.

20 If the CPU 1 determines in step S2 that the user code has been specified, in step S3, the CPU 1 operates as registration determination means to determine whether one or more subject names have been registered for the specified user code. If one or

25 more subject names have been registered, the

operation proceeds to step S4, and if not, the operation proceeds to step S5. In step S4, the CPU 1 operates as subject name specifying means to perform an operation for employing one of the registered
5 subject names as a subject name at the time of mail transmission. The subject name employed at the time of mail transmission is referred to as the "transmission subject name." For instance, in step S4, the CPU 1 may employ the first one of the
10 registered subject names as the transmission subject name in a default state. Thereafter, the operation proceeds to step S19.

Thus, the facsimile machine 20 automatically specifies one of the previously registered subject
15 names as the transmission subject name if no subject name is specified at the time of transmitting mail data. Therefore, for instance, if the same subject name such as "Circular Document" or "Weekly Report" is employable for every mail transmission, the
20 facsimile machine 20 does not have to repeat an input operation for specifying the same subject name every time mail transmission is performed. This makes the facsimile machine 20 easy to use.

On the other hand, in step S5, the CPU 1
25 determines which subject name to use in

correspondence to the user code. That is, the CPU 1 determines whether there has been a subject name specified for preferential use. If there has been a subject name specified for preferential use, the operation proceeds to step S6, and if not, the operation proceeds to step S8. In step S6, the CPU 1 determines whether the subject name specified for preferential use has been registered. If the subject name specified for preferential use has been registered, the operation proceeds to step S7, and if not, the operation proceeds to step S8. In step S7, the CPU 1 performs an operation for employing the registered specified subject name as the transmission subject name. Then, the operation proceeds to step S19.

Thus, the facsimile machine 20 allows the operator to previously select the subject name to be automatically employed from the registered subject names with respect to each user code. The facsimile machine 20 also allows the operator to specify the priority of each subject name to be automatically employed. This provides the operator with more latitude in operating the facsimile machine 20, thus making the facsimile machine 20 easy to use. The subject name to be automatically employed can be

registered so as to correspond to the user code.
Therefore, the facsimile machine 20 allows a
plurality of operators to freely use the respective
subject names corresponding to their user codes
5 independent of one another. This also makes the
facsimile machine 20 easy to use.

The operation proceeds to step S8 in any of
the following cases: (a) the user code has not been
specified, (b) no subject name has been registered
10 and no subject name has been specified for
preferential use although the user code has been
specified, and (c) a subject name has been specified
for preferential use but has not been registered. In
any of these cases, in step S8, the CPU 1 performs an
15 operation of retrieving a subject name to be employed
as the transmission subject name from a plurality of
subject names previously registered or stored in the
facsimile machine 20. This retrieving operation may
be performed by determining the first (leading) one
20 of the subject names as the subject name to be
employed, or by the operator previously determining
what number subject name is to be employed and
determining the subject name corresponding to that
number as the subject name to be employed.
25 Alternatively, the operator may previously determine

the priorities of subject names to be employed,
search the registered subject names in accordance
with the priorities, and determine the first
retrieved one of the registered subject names as the
5 subject name to be employed.

After performing the retrieving operation in
step S8, the operation proceeds to step S9, where the
CPU 1 determines whether the subject name to be
employed has been retrieved. If an employable
10 subject name, that is, the subject name to be
employed, has been retrieved, in step S10, the CPU 1
performs an operation for employing the subject name
to be employed as the transmission subject name.
Thereafter, the operation proceeds to step S19. If
15 the subject name to be employed has not been
retrieved, the operation proceeds to step S11 of FIG.
3B, where the CPU 1 again determines whether the user
code has been specified. If the user code has been
specified, the operation proceeds to step S12, and if
20 not, the operation proceeds to step S16. In step S12,
the CPU 1 operates as address registration
determination means to determine whether the
specified user code has a corresponding mail address
registered as a distribution destination. If the
25 specified user code has a corresponding mail address

registered, the operation proceeds to step S13, where the CPU 1 performs an operation for creating a subject name using the registered mail address, and employing the created subject name as the

5 transmission subject name. Thereafter, the operation proceeds to step S19 of FIG. 3A. The subject name created using the registered mail address may be one such as "From (the mail address of the distribution destination)."

10 On the other hand, if the CPU 1 determines in step S12 that the specified user code has no corresponding mail address registered as a distribution destination, the operation proceeds to step S14, where the CPU 1 operates as name
15 registration determination means to determine whether the specified user code has a corresponding name registered. If the specified user code has a corresponding name registered, the operation proceeds to step S15, and if not, the operation proceeds to
20 step S16. In step S15, the CPU 1 performs an operation for creating a subject name using the registered user code name, and employing the created subject name as the transmission subject name. Thereafter, the operation proceeds to step S19 of FIG.
25 3A. The subject name created using the user code

name may be one such as "From (the user code name)."

The operation proceeds to step S16 if (a) the user code name has not been registered or (b) the subject name to be employed has not been determined
5 from among the previously registered (stored) subject names and the user code has not been specified, either. In step S16, the CPU 1 determines whether transmitter information such as the facsimile number or the name of the transmitter has been registered.
10 If the transmitter information has been registered, the operation proceeds to step S17, and if not, the operation proceeds to step S18. In step S17, the CPU 1 performs an operation for creating a subject name using the registered transmitter information, and
15 employing the created subject name as the transmission subject name. The subject name created using the transmitter information may be as follows. If both facsimile number and name of the transmitter are registered, the subject name is "From (the
20 facsimile number or the name of the transmitter)."
If only the facsimile number of the transmitter is registered, the subject name is "From (the facsimile number of the transmitter)." If only the name of the transmitter is registered, the subject name is "From
25 (the name of the transmitter)." If no transmitter

information has been registered, in step S18, the CPU
1 performs an operation for creating a subject name
where no registered information is used, such as "Fax
Message," and employing the created subject name as
5 the transmission subject name. Then, the operation
proceeds to step S19 of FIG. 3A.

Thus, if the subject name to be employed is
not determined after searching the registered or
stored subject names, the facsimile machine 20 can
10 create the subject name using the mail address of a
distribution destination registered in correspondence
to the user code. Accordingly, even if there is no
particular need to specify the subject name, the
receiver can identify the transmitter of the mail by
15 its subject name including the mail address of the
transmitter. Even if no mail address is registered,
it is possible to create the subject name using the
user code name registered in correspondence to the
user code. Therefore, the receiver can identify the
20 transmitter of the mail by its subject name including
the user code name of the transmitter. In this case,
compared with the case of the subject name including
the mail address, in which name information is not
necessarily included, the transmitter can be
25 identified more easily, thereby increasing

convenience.

By the above-described operation, the facsimile machine 20 automatically determines the transmission subject name without the operator specifying the subject name. After the transmission subject name is determined, the operation proceeds to step S19, where the CPU 1 displays the transmission subject name determined through the previous steps on the operation display 4. This allows the operator to confirm the contents of the transmission subject name. Then, the operator determines the appropriateness of the contents of the transmission subject name. As a result of the determination, the operator determines the necessity of editing (correcting) the transmission subject name, and the operator inputs information showing the necessity of the editing or correction by operating the operation display 4. Receiving the input information, the CPU 1 causes the operation to proceed to step S20, where the CPU 1 determines whether the editing of the transmission subject name has been requested. If the editing has been requested, in step S21, the CPU 1 edits the transmission subject name according to the input operation by the operation display 4. If the editing has not been requested, the CPU 1 terminates the

operation without performing step S21. Accordingly, the contents of the transmission subject name finally obtained reflect the results of the editing by the operator.

5 According to the present invention, the subject name can be specified by any of the following operations. First, the subject name can be newly input from scratch and be specified. This is suitable for the case of changing the subject name of
10 mail data in every transmission. Second, one of previously registered subject names may be cited and employed as such. Third, one of the subject names previously registered (stored) in the RAM 3 may be cited, and edited as required to be employed as the
15 subject name. This method is used in the case of creating a partially fixed subject name such as "Monthly Report (2001/11/30)" or "Daily Report (2001/12/01)."

 Thus, if the subject name is not specified
20 at the time of starting a transmission operation and is automatically determined, the facsimile machine 20 displays the determined subject name after the start key for starting transmission is pressed. Accordingly, the operator can check the subject name
25 to be employed as the transmission subject name,

which is convenient for the operator. Further, the subject name is editable as required. Therefore, even if the contents of the subject name are not as desired due to wrong input, it is possible to re-
5 specify the subject name. This is also a convenient feature of the facsimile machine 20 for the operator.

Furthermore, it is possible to cite one of a plurality of previously stored subject names and edit the cited subject name. Therefore, even if the
10 contents of the subject name are partially the same in every transmission, such as "Circular Document (2001/12/01)" or "Weekly Report (2001/12/07)", the subject name can be input with minimum required editing. This makes the facsimile machine 20 easy to
15 use.

As previously described, the network facsimile machine according to the present invention automatically specifies the subject name without the operator performing an operation for specifying the
20 subject name. Therefore, this network facsimile machine is easy to use.

The present invention is not limited to the specifically disclosed embodiment, and variations and modifications may be made without departing from the
25 scope of the present invention.

The present application is based on Japanese priority application No. 2002-227339, filed on August 5, 2002, the entire contents of which are hereby incorporated by reference.